

**CONBRACO™
HEATING SPECIALTIES**



**LOW-PRESSURE STEAM
BOILER SAFETY VALVE
-STANDARD-**

W-R#	Size	Conbraco#	PSI	BTU
1727001	3/4"	13-511-08	15	407
1727000	3/4"	13-211-08	15	475
1727002	1"	13-202-08	15	643
1727004	1 1/4"	13-213-08	15	1200
1727006	1 1/2"	13-214-08	15	1900
1727008	2"	12-205-08	15	2500
1727010	2 1/2"	12-206-08	15	3529
1727012	3"	12-208-08	15	4100



**LOW-PRESSURE STEAM
BOILER SAFETY VALVE
-HI-CAPACITY-**

W-R#	Size	Conbraco#	PSI	BTU
1727606	2"	14-205-08	15	3150
1727608	2 1/2"	14-206-08	15	4676
1727610	3"	14-207-08	15	6843



**3/4" A.S.M.E. SAFETY
RELIEF VALVE FOR
HOT WATER BOILERS**

W-R#	Size	Conbraco#	PSI
1725008	3/4" F x F	10-408-05	30
1725006	3/4" M x F	10-407-05	30
1725009	3/4" M x F	10-407-09	45

- Maximum temperature: 250°F



**PRESSURE
RELIEF VALVE**

W-R#	Size	Conbraco#	PSI
1725002	1/2" M x F	16-202-04	125

- Relieves excess pressure in water supply lines.



**WATER HEATER
RELIEF VALVE**

W-R#	Size	Conbraco#	PSI
1725504	3/4" M x F	18-402-30	150

- 4" Element

- For temperature & pressure relief protection on domestic hot water heaters and storage tanks. ASME rated.



**CONBRACO™
HEATING SPECIALTIES**



**DOUBLE FEMALE
AIRCOCK**

W-R#	Size	Conbraco#	Min
1702002	1/8"	41-370-01	1 25
1702004	1/4"	41-380-01	1 25

- Satin Brass
- Spring Bottom



MALE PETCOCK

W-R#	Size	Conbraco#	Min
1703002	1/8"	41-060-01	1 25
1703004	1/4"	41-070-01	1 25

- Satin Brass
- Spring Bottom



**MALE X FEMALE
AIRCOCK**

W-R#	Size	Conbraco#	Min
1704002	1/8"	41-400-01	1 25
1704004	1/4"	41-410-01	1 25
1704005	3/8"	41-420-01	1 25

- Satin Brass
- Spring Bottom



**STANDARD
ROUGH BRONZE
WATER GAUGE SETS**

W-R#	Size	Conbraco#
1723004	3/8"	20-101-00
1723006	1/2"	20-104-00

- Service Rating: 125 psi @ 300°F, -300 psi @ 100°F
- Furnished with 5/8" x 10 standard glass
- Aluminum Wheel
- Features 1/4" Needle drain valve in lower arm.



**COMPRESSION GAUGE
COCK
(TRICOCK)**

W-R#	Size	Conbraco#
1704204	1/2"	26-104-01

- 125 psi
- Aluminum Wheel



**CONBRACO™
HEATING SPECIALTIES**




**BRONZE MANUAL MAIN
CONTROL VALVES**

W-R#	Size	Conbraco#
0413500	1/2"	50-203-02
0413502	3/4"	50-303-02
0413504	1"	50-403-02
0413506	1 1/4"	50-503-02
0413508	1 1/2"	50-603-02
0413510	2"	50-703-02

- Temperature range: 32°F-125°F
- Meets ANS Z 21.15 requirements of 1/2" psi
- Furnished with 1/8" pilot tapping



**BRONZE BALL-CONE®
CHECK VALVES**



Patented design offers exceptional resistance to chemicals & corrosion.

W-R#	Size	Conbraco#
0412902	1/4"	61-101-01
0412904	3/8"	61-102-01
0412906	1/2"	61-103-01
0412908	3/4"	61-104-01
0412910	1"	61-105-01
0412912	1 1/4"	61-106-01
0412914	1 1/2"	61-107-01
0412916	2"	61-108-01

- Open pressure: 1/2 psi
- 125 psig steam rating
- Not recommended for use on reciprocating pumps or other applications that induce repetitious vibrations.



**ATMOSPHERIC
ANTI-SIPHON
VACUUM BREAKERS**

W-R#	Size	Finish	Conbraco#
0413001	3/8"	Chrome	38-102-03
0413002	1/2"	Rough Br	38-103-01
0413003	1/2"	Chrome	38-103-03
0413004	3/4"	Rough Br	38-104-01
0413006	1"	Rough Br	38-105-01

- For hot & cold water service
- Up to 212°F at 125 psi



**"APOLLO" 70-SERIES
BALL VALVES**

W-R#	Size	Conbraco#
0412002	1/2"	IPS 70-103-01
0412004	3/4"	IPS 70-104-01
0412006	1"	IPS 70-105-01
0412008	1 1/4"	IPS 70-106-01
0412010	1 1/2"	IPS 70-107-01
0412012	2"	IPS 70-108-01

